

SOMO EZ-View Mini Aspheric Polycarbonate Progressive

Characteristic & Technical Data

- * **Aspheric Design** : All regions of the lens are aspheric..
- * **Wide Reading Zone** : It has a wide field of view and comfortable use in the near zones.
- * **Asymmetry design** : Gives minimum distortions and reduces the distortions in the peripheral zones to provide a comfortable wear.
- * **Multidesign** : Every base and addition is optimally designed to improve optimum vision.
- * **Distortion** : The lens design gives minimal distortion.
- * **Corridor** : The corridor zone is especially wide, enabling comfortable eye movement between the reading zone and the distance zone. The full addition length is 13mm from GC.
- * **Discentration** : The optical center of the lens is off from the GC by 3.0 mm (from right or left).

Base Curve	2.75	4.75	6.75	7.75
True Curve	2.93	4.85	6.76	7.71
Back Curve	-6.25	-6.25	-6.25	-6.25
Diameter (mm)	75	75	75	75
Edge Thickness	13.2	9.2	8.8	6.8
Center Thickness	7.2	7.4	8.0	10.5
Power Range	-8.00~-2.75	-2.50~+1.75	+2.00~+3.50	+3.75~+8.00
Addition	+1.00~+3.00	+1.00~+3.00	+1.00~+3.00	+1.00~+3.00

Note: It is recommended the minimum fitting height for SOMO EZ View Mini is 16mm.

