

TECHNICAL CHART

TRIVEX® SPHERICAL

CYL (- ON -) - 0.00 ~ - 2.00					POWER	CYL (+ ON -) - 0.00 ~ - 2.00					
DIA- (mm)	E/T (mm)	C/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA- (mm)	
Φ70	2.00	2.00	4.25	4.25	0.00						
	2.30			4.00	0.25	4.25	4.00	2.60	2.30	Φ65	
	2.60			3.75	0.50	4.50		2.00			
	2.90			3.50	0.75	4.75		2.50	1.70		
	3.10	1.90		3.25	1.00	5.00		1.40			
	3.40			3.00	1.25	4.50	2.90	1.60			
	3.60	1.80		5.00	3.50	1.50	4.75	3.25	3.10		1.50
	3.90				3.25	1.75	5.00		3.30		1.20
	4.10	1.70	3.00		2.00	5.25	3.00		3.60		
	4.30		2.75		2.25	5.50			3.80		
	4.70	1.60	5.25		2.50	2.50		5.75	4.10		
	4.90				2.25	2.75		6.00	4.30	1.00	
	5.10	1.50			2.00	3.00		6.25	4.50	1.10	
	5.40				1.75	3.25		6.50	4.80	1.10	
	5.70			5.75	2.00	3.50		6.75	5.00	1.00	
	6.10				1.75	4.00		7.00	5.30		
	6.40				1.50	4.25	TOLERANCE C/T: +/- 0.3mm Diameter: +1.00mm/-0.5mm				
	6.70				1.25	4.50					
	7.00		1.00	4.75							
	7.20		6.35	1.35	5.00						
	7.60			1.10	5.25						
	7.90			0.85	5.50						
	8.20			0.60	5.75						
	8.50		0.35	6.00							
8.80											