

# TECHNICAL CHART HI-INDEX 1.56 SPHERICAL

CYL ( - ON - ) - 0.00 ~ - 2.00					POWER	CYL ( + ON - ) - 0.00 ~ - 2.00					
DIA- (mm)	E/T (mm)	C/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA- (mm)	
Φ72	2.0	2.0	4.40	4.40	0.00						
	1.8	1.5		4.40	4.15	0.25	4.55	4.30	1.8	1.5	Φ65
	2.2				3.90	0.50	4.80		2.1		
	2.5				3.65	0.75	5.05		2.3		
	2.9				3.40	1.00	4.30	3.30	2.1		
	2.9				3.15	1.25	4.55		2.4		
	3.2	1.2	5.50	2.90	1.50	4.80	2.6				
	3.5			3.75	1.75	5.05	2.9				
	3.9	1.2	5.50	3.50	2.00	5.30	3.2	1.2			
	4.2			3.25	2.25	5.55	3.5				
	4.5			3.00	2.50	5.80	3.6				
	4.8			2.75	2.75	6.05	3.9				
	5.1			2.50	3.00	5.30	2.30		4.1		
	5.7	1.2	6.60	3.35	3.25	5.55		4.4			
	6.0			3.10	3.50	5.80		4.6			
	6.3			2.85	3.75	6.05		4.8			
	6.6			2.60	4.00	6.30	5.1				
	6.9			2.35	4.25	1. "MINUS" LENS SPH AXIS : -0.00 ~ -8.00 CYL AXIS : -0.00 ~ -2.00 2. "PLUS" LENS SPH AXIS : +0.25 ~ +4.00 CYL AXIS : -0.00 ~ -2.00 3. TOLERANCE ( ± 0.3 mm ) CENTER- EDGE THICKNESS					
	7.2			3.20	4.50						
	7.8	1.2	7.70	2.95	4.75						
	8.1			2.70	5.00						
	8.4			2.45	5.25						
	8.7			2.20	5.50						
	9.0			1.95	5.75						
	9.3			1.70	6.00						
	9.0	1.2	7.70	1.45	6.25						
	9.3			1.20	6.50						
	9.6			0.95	6.75						
9.9	0.70			7.00							
10.6	8.80		1.55	7.25							
10.8		1.30	7.50								
11.1		1.05	7.75								
11.4		0.80	8.00								