

TECHNICAL CHART POLYCARBONATE ASPHERIC

CYL (- ON -) - 0.00 ~ - 2.00					POWER	CYL (+ ON -) - 0.00 ~ - 2.00								
DIA- (mm)	E/T (mm)	C/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA- (mm)				
					0.00									
					0.25	3.88	3.65	1.50	1.00	Φ68				
					0.50		3.43	1.70						
					0.75		3.20	1.80						
					1.00		2.97	2.00						
					1.25		2.75	2.10						
					1.50		2.53	2.40						
					1.75		2.33	2.60						
					2.00		2.10	2.90						
					2.25		4.20	2.22			2.90			
					2.50			2.00			3.20			
					2.75	1.78		3.40						
					3.00	1.56		3.60						
					3.25	1.33		3.87						
					3.50	5.28	2.20	4.05						
					3.75		1.98	4.29						
					4.00		1.76	4.53						
					4.25		1. Plus lenses are referred to edge thickness at spherical power edge. 2. Center thickness tolerance shall be less than +/- 0.3mm 3. Diameter tolerance shall be less than +1.0mm / -0.5mm							
					4.50									
					4.75									
					5.00									
					5.25									
					5.50									
					5.75									
					6.00									
					6.25	Φ72						1.20	5.88	0.23
					6.50								6.10	
					6.75		6.33							
7.00	6.56													
7.25	6.79													
7.50	7.01													
7.75	7.24													
8.00	7.47													