

## TECHNICAL CHART POLYCARBONATE ASPHERIC

CYL ( - ON - ) - 0.00 ~ - 3.00					POWER	CYL ( + ON - ) - 0.00 ~ - 2.00				
DIA- (mm)	E/T (mm)	C/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA- (mm)
Φ72	2.0	2.0	3.85	3.83	0.00					
	2.0	1.7	4.07	3.83	0.25	3.88	3.65	2.0	1.8	Φ68
	2.3		4.30	3.83	0.50	3.88	3.43	2.2		
	2.6		4.52	3.83	0.75	3.88	3.20	2.3	1.6	
	2.9		4.75	3.83	1.00	3.88	2.97	2.5		
	3.2		4.98	3.83	1.25	3.88	2.75	2.6	1.4	
	3.5		1.4	5.20	3.83	1.50	3.88	2.53		
	3.4	3.61			1.75	3.88	2.33	2.6	1.0	
	3.6	3.38			2.00	3.88	2.10	2.9		
	3.9	3.16			2.25	4.20	2.22	2.9		
	4.2	2.93			2.50	4.20	2.00	3.1		
	4.5	3.16			2.75	4.20	1.78	3.4		
	4.8	1.3	5.65	2.93	3.00	4.20	1.56	3.6		
	5.0			2.70	3.25	4.20	1.33	3.9		
	5.2			2.48	3.50	5.28	2.20	4.0		
	5.5			2.26	3.75	5.28	1.98	4.3		
	5.8			2.03	4.00	5.28	1.76	4.5		
	5.9			1.2	6.10	1.80	4.25	5.55	1.80	
	6.3	2.03	4.50			5.78	4.3			
	6.5	1.80	4.75			6.00	4.4			
	6.8	1.58	5.00			5.78	1.35	4.6		
	7.0	1.35	5.25			6.00		4.8		
	7.3	1.13	5.50			6.22		5.0		
	7.5	0.90	5.75	6.00	0.90	5.2				
7.7	0.68	6.00	6.22	5.4						
Φ72 CYL -0.00 ~ -2.00	8.3	1.2	6.56	0.90	6.25	1. "MINUS" LENS SPH: -0.00 ~ -6.00/-8.00 CYL: -0.00 ~ -3.00/-2.00 2. "PLUS" LENS SPH: +0.25 ~ +6.00 CYL: -0.00 ~ -2.00 3. TOLERANCE C/T: +/- 0.3mm Diameter: +1.00mm/-0.5mm				
	8.5			0.68	6.50					
	8.8			0.46	6.75					
	9.0			0.23	7.00					
	9.5		7.01	0.46	7.25					
	9.7			0.23	7.50					
	10.2		7.47	0.46	7.75					
	10.4			0.23	8.00					