

## TECHNICAL CHART TRIVEX® SPHERICAL

CYL ( - ON - ) - 0.00 ~ - 2.00					POWER	CYL ( + ON - ) - 0.00 ~ - 2.00							
DIA- (mm)	E/T (mm)	C/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA- (mm)			
Φ70	2.00	2.00	4.25	4.25	<b>0.00</b>								
	2.30			4.00	<b>0.25</b>	4.25	4.00	2.60	2.30	Φ65			
	2.60			3.75	<b>0.50</b>	4.50		2.00					
	2.90			3.50	<b>0.75</b>	4.75		2.50	1.70				
	3.10	1.90		3.25	<b>1.00</b>	5.00		1.40					
	3.40			3.00	<b>1.25</b>	4.50	2.90	1.60					
	3.60	1.80		5.00	3.50	<b>1.50</b>	4.75	3.25	3.10		1.50		
	3.90				3.25	<b>1.75</b>	5.00		3.30		1.20		
	4.10	1.70	3.00		<b>2.00</b>	5.25	3.00		3.60			1.10	
	4.30		2.75		<b>2.25</b>	5.50			3.80				
	4.70	1.60	5.25		2.50	<b>2.50</b>		5.75	4.10		1.00		
	4.90				2.25	<b>2.75</b>		6.00	4.30				
	5.10	1.50			5.75	2.00		<b>3.00</b>	6.25		4.50		
	5.40					1.75		<b>3.25</b>	6.50		4.80	1.10	
	5.70			2.00		<b>3.50</b>		6.75	5.00		1.00		
	6.10			1.75		<b>4.00</b>		7.00	5.30				
	6.40			6.35	5.75	1.50	<b>4.25</b>	TOLERANCE C/T: +/- 0.3mm Diameter: +1.00mm/-0.5mm					
	6.70					1.25	<b>4.50</b>						
	7.00		1.00			<b>4.75</b>							
	7.20		1.35			<b>5.00</b>							
	7.60		1.10		<b>5.25</b>								
	7.90		0.85		<b>5.50</b>								
	8.20		0.60		<b>5.75</b>								
	8.50		0.35		<b>6.00</b>								
8.80													