

TECHNICAL CHART

POLY SUNSMART PHOTO-GRAY PREMIUM AR

CYL (- ON -) - 0.00 ~ - 2.00					POWER	CYL (+ ON -) - 0.00 ~ - 2.00						
DIA- (mm)	E/T (mm)	C/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA- (mm)		
Φ72	2.03	2.00	3.85	3.83	0.00					Φ68		
	2.11	1.80	4.07		0.25						3.88	3.88
	2.41		4.30		0.50	3.43	2.30					
	2.70		4.52		0.75	3.20	2.40	1.60				
	3.00		4.75		1.00	2.97	2.60					
	3.31	4.98	1.25		2.75	2.70	1.40					
	3.30	1.50	5.20		1.50	2.53		2.90				
	3.52	1.40	5.43		1.75	4.20	4.20	2.33	2.70		1.00	
	3.82		5.65		2.00			2.10	3.00			
	4.14		5.88		2.25			2.22	3.20			
	4.44		6.10		2.50			2.00	3.50			
	4.77	6.33	2.75		5.28	5.28	5.28	1.78	3.70			
	5.10	6.56	3.00					1.56	4.00			
	5.38	1.30	7.01					4.04	3.25		1.33	4.20
	5.66							3.83	3.50		2.20	4.50
	5.94		7.00		3.60	3.75	1.98	4.80				
	6.23		7.01		3.38	4.00	1.76	5.00				
	6.51	1.20	7.45		3.60	4.25	1. "MINUS" LENS SPH: -0.00 ~ -6.00 CYL: -0.00 ~ -2.00 2. "PLUS" LENS SPH: +0.25 ~ +4.00 CYL: -0.00 ~ -2.00 3. TOLERANCE C/T: +/- 0.3mm Diameter: +1.00mm/-0.5mm					
	6.81		7.46		3.38	4.50						
	7.10					3.15						4.75
7.38	2.93			5.00								
7.80	7.91		3.15	3.15	5.25							
8.07				2.93	5.50							
8.36				2.70	5.75							
8.64				2.48	6.00							