

TECHNICAL CHART

POLYCARBONATE ASP TRANSITIONS S GREY TOP CLEAN+UV

CYL (- ON -) - 0.00 ~ - 2.00					POWER	CYL (+ ON -) - 0.00 ~ - 2.00				
DIA- (mm)	E/T (mm)	C/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA- (mm)
Φ70	2.00	2.00	3.37	3.38	0.00					
	2.10	1.90	3.16	3.16	0.25	3.38	3.14			
	2.35		2.03	3.38	0.50	3.60		1.50		
	2.60	1.80	1.36	3.16	0.75	3.38	2.69	1.30		
	2.75		3.38	3.38	1.00	3.60		1.90	1.00	
	3.00	1.70	4.26	3.16	1.25	3.37	2.24	2.00	Φ65	
	3.25		4.71	3.38	1.50	3.60		2.20		
	3.40	1.60	4.71	3.16	1.75	3.37	1.79	2.50		
	3.65			5.16	3.38	2.00		3.60		2.70
	3.80		4.26	2.26	2.25	4.26		2.22		2.90
	4.05	1.50		2.03	2.50	4.47	2.21	3.10		
	4.30		4.71	2.26	2.75	4.26	1.77	3.40		
	4.45	5.16		2.03	3.00	4.47	1.76	3.60		
	4.85		2.26	3.25	5.13	2.18	3.80			
	5.05		2.03	3.50	5.34	2.17	4.00			
	5.15	4.72	1.36	3.75	5.13	1.74	4.30	1.20		
	5.45		1.13	4.00	5.34	1.72	4.50			
	5.75	1.40	5.17	1.36	4.25	1. Plus lenses are referred to edge thickness at spherical power edge. 2. Center thickness tolerance shall be less than +/- 0.3mm 3. Diameter tolerance shall be less than +2.0mm / -1.0mm (70mm dia) & less than +1.0mm/-1.0mm (65mm dia)				
	5.95			1.13	4.50					
	6.35	5.62	1.36	4.75						
	6.55	5.61	1.13	5.00						
	6.85		0.90	5.25						
	7.05		0.68	5.50						
	7.45	6.06	0.90	5.75						
	7.65		0.68	6.00						